

# Classification Of Low-Alloy Electrodes As Per AWS A5.5-96

E 9018-B3																																																																																																																																																																														
<table border="1"> <thead> <tr> <th colspan="2">Production Type</th> </tr> </thead> <tbody> <tr> <td>G</td> <td>Wire Electrodes</td> </tr> <tr> <td>O</td> <td>Oxy-Acetylene</td> </tr> <tr> <td>E</td> <td>Electric Arc Welding</td> </tr> <tr> <td>S</td> <td>Submerged Arc</td> </tr> <tr> <td>T</td> <td>Flux-Cored Wires</td> </tr> <tr> <td>W</td> <td>TIG Rods</td> </tr> <tr> <td>F</td> <td>Submerged Arc</td> </tr> </tbody> </table>		Production Type		G	Wire Electrodes	O	Oxy-Acetylene	E	Electric Arc Welding	S	Submerged Arc	T	Flux-Cored Wires	W	TIG Rods	F	Submerged Arc	<table border="1"> <thead> <tr> <th>Symbol</th> <th>Type of Cover</th> <th>Welding Positions</th> <th>Type Of Current</th> </tr> </thead> <tbody> <tr> <td>10</td> <td>Cellulosic Sodium Sillicate</td> <td>F,V,OH,H-Fillet</td> <td>DC (+)</td> </tr> <tr> <td>11</td> <td>Cellulosic Potassium Sillicate</td> <td>F,V,OH,H-Fillet</td> <td>AC DC (+)</td> </tr> <tr> <td>13</td> <td>Rutile Potassium Sillicate</td> <td>F,V,OH,H-Fillet</td> <td>AC DC (-) (+)</td> </tr> <tr> <td>15</td> <td>Basic Sodium Sillicate</td> <td>F,V,OH,H-Fillet</td> <td>DC (+)</td> </tr> <tr> <td>16</td> <td>Basic Potassium Sillicate</td> <td>F,V,OH,H-Fillet</td> <td>AC DC (+)</td> </tr> <tr> <td>18</td> <td>Basic Iron Powder Potassium Sillicate</td> <td>F,V,OH,H-Fillet</td> <td>AC DC (+)</td> </tr> <tr> <td>20</td> <td>Iron Oxide</td> <td>F, H-Fillet</td> <td>AC DC (-) (+)</td> </tr> <tr> <td>27</td> <td>Iron Oxide Powder</td> <td>Iron F, H-Fillet</td> <td>AC DC (-) (+)</td> </tr> </tbody> </table>			Symbol	Type of Cover	Welding Positions	Type Of Current	10	Cellulosic Sodium Sillicate	F,V,OH,H-Fillet	DC (+)	11	Cellulosic Potassium Sillicate	F,V,OH,H-Fillet	AC DC (+)	13	Rutile Potassium Sillicate	F,V,OH,H-Fillet	AC DC (-) (+)	15	Basic Sodium Sillicate	F,V,OH,H-Fillet	DC (+)	16	Basic Potassium Sillicate	F,V,OH,H-Fillet	AC DC (+)	18	Basic Iron Powder Potassium Sillicate	F,V,OH,H-Fillet	AC DC (+)	20	Iron Oxide	F, H-Fillet	AC DC (-) (+)	27	Iron Oxide Powder	Iron F, H-Fillet	AC DC (-) (+)	<table border="1"> <thead> <tr> <th>Symbol</th> <th>Elongation % Min</th> </tr> </thead> <tbody> <tr> <td>E 7010</td> <td>P1/A/G 22/22/22</td> </tr> <tr> <td>E7011</td> <td>A1/G 22/22</td> </tr> <tr> <td>E7015</td> <td>X/B2L/G 25/19/25</td> </tr> <tr> <td>E7016</td> <td>X/B2L/G 25/19/25</td> </tr> <tr> <td>E 7018</td> <td>X/B2L/C3L/W1/G 25/19/25/25/25</td> </tr> <tr> <td>E7020</td> <td>A1/G 25/25</td> </tr> <tr> <td>E7027</td> <td>A1/G 22/25</td> </tr> <tr> <td>E8010</td> <td>P1/G 19/19</td> </tr> <tr> <td>E8011</td> <td>G 19</td> </tr> <tr> <td>E8013</td> <td>G 16</td> </tr> <tr> <td>E8015</td> <td>X/B3L/G 19/17/19</td> </tr> <tr> <td>E8016</td> <td>X/C3/C4/G 19/24/19/19</td> </tr> <tr> <td>E8018</td> <td>X/B3L/C3/C4/ NM1/W2/G 19/17/24/19/19/19/19</td> </tr> <tr> <td>E9010</td> <td>G 17</td> </tr> <tr> <td>E9011</td> <td>G 17</td> </tr> <tr> <td>E9013</td> <td>G 14</td> </tr> <tr> <td>E9015</td> <td>X/G 17/17</td> </tr> <tr> <td>E9016</td> <td>X/G 17/17</td> </tr> <tr> <td>E9018</td> <td>M/X/G 24/17/17</td> </tr> <tr> <td>E10010</td> <td>G 16</td> </tr> <tr> <td>E10011</td> <td>G 16</td> </tr> <tr> <td>E10013</td> <td>G 13</td> </tr> <tr> <td>E10015</td> <td>X/G 16/16</td> </tr> <tr> <td>E10016</td> <td>X/G 16/16</td> </tr> <tr> <td>E10018</td> <td>M/X/G 20/16/16</td> </tr> <tr> <td>E11010</td> <td>G 15</td> </tr> <tr> <td>E11011</td> <td>G 15</td> </tr> <tr> <td>E11013</td> <td>G 13</td> </tr> <tr> <td>E11015</td> <td>G 15</td> </tr> <tr> <td>E11016</td> <td>G 15</td> </tr> <tr> <td>E11018</td> <td>M 20</td> </tr> <tr> <td>E12010</td> <td>G 14</td> </tr> <tr> <td>E12011</td> <td>G 14</td> </tr> <tr> <td>E12013</td> <td>G 11</td> </tr> <tr> <td>E12015</td> <td>G 14</td> </tr> <tr> <td>E12016</td> <td>G 14</td> </tr> <tr> <td>E12018</td> <td>G/M/M1 14/18/18</td> </tr> </tbody> </table>		Symbol	Elongation % Min	E 7010	P1/A/G 22/22/22	E7011	A1/G 22/22	E7015	X/B2L/G 25/19/25	E7016	X/B2L/G 25/19/25	E 7018	X/B2L/C3L/W1/G 25/19/25/25/25	E7020	A1/G 25/25	E7027	A1/G 22/25	E8010	P1/G 19/19	E8011	G 19	E8013	G 16	E8015	X/B3L/G 19/17/19	E8016	X/C3/C4/G 19/24/19/19	E8018	X/B3L/C3/C4/ NM1/W2/G 19/17/24/19/19/19/19	E9010	G 17	E9011	G 17	E9013	G 14	E9015	X/G 17/17	E9016	X/G 17/17	E9018	M/X/G 24/17/17	E10010	G 16	E10011	G 16	E10013	G 13	E10015	X/G 16/16	E10016	X/G 16/16	E10018	M/X/G 20/16/16	E11010	G 15	E11011	G 15	E11013	G 13	E11015	G 15	E11016	G 15	E11018	M 20	E12010	G 14	E12011	G 14	E12013	G 11	E12015	G 14	E12016	G 14	E12018	G/M/M1 14/18/18																																								
Production Type																																																																																																																																																																														
G	Wire Electrodes																																																																																																																																																																													
O	Oxy-Acetylene																																																																																																																																																																													
E	Electric Arc Welding																																																																																																																																																																													
S	Submerged Arc																																																																																																																																																																													
T	Flux-Cored Wires																																																																																																																																																																													
W	TIG Rods																																																																																																																																																																													
F	Submerged Arc																																																																																																																																																																													
Symbol	Type of Cover	Welding Positions	Type Of Current																																																																																																																																																																											
10	Cellulosic Sodium Sillicate	F,V,OH,H-Fillet	DC (+)																																																																																																																																																																											
11	Cellulosic Potassium Sillicate	F,V,OH,H-Fillet	AC DC (+)																																																																																																																																																																											
13	Rutile Potassium Sillicate	F,V,OH,H-Fillet	AC DC (-) (+)																																																																																																																																																																											
15	Basic Sodium Sillicate	F,V,OH,H-Fillet	DC (+)																																																																																																																																																																											
16	Basic Potassium Sillicate	F,V,OH,H-Fillet	AC DC (+)																																																																																																																																																																											
18	Basic Iron Powder Potassium Sillicate	F,V,OH,H-Fillet	AC DC (+)																																																																																																																																																																											
20	Iron Oxide	F, H-Fillet	AC DC (-) (+)																																																																																																																																																																											
27	Iron Oxide Powder	Iron F, H-Fillet	AC DC (-) (+)																																																																																																																																																																											
Symbol	Elongation % Min																																																																																																																																																																													
E 7010	P1/A/G 22/22/22																																																																																																																																																																													
E7011	A1/G 22/22																																																																																																																																																																													
E7015	X/B2L/G 25/19/25																																																																																																																																																																													
E7016	X/B2L/G 25/19/25																																																																																																																																																																													
E 7018	X/B2L/C3L/W1/G 25/19/25/25/25																																																																																																																																																																													
E7020	A1/G 25/25																																																																																																																																																																													
E7027	A1/G 22/25																																																																																																																																																																													
E8010	P1/G 19/19																																																																																																																																																																													
E8011	G 19																																																																																																																																																																													
E8013	G 16																																																																																																																																																																													
E8015	X/B3L/G 19/17/19																																																																																																																																																																													
E8016	X/C3/C4/G 19/24/19/19																																																																																																																																																																													
E8018	X/B3L/C3/C4/ NM1/W2/G 19/17/24/19/19/19/19																																																																																																																																																																													
E9010	G 17																																																																																																																																																																													
E9011	G 17																																																																																																																																																																													
E9013	G 14																																																																																																																																																																													
E9015	X/G 17/17																																																																																																																																																																													
E9016	X/G 17/17																																																																																																																																																																													
E9018	M/X/G 24/17/17																																																																																																																																																																													
E10010	G 16																																																																																																																																																																													
E10011	G 16																																																																																																																																																																													
E10013	G 13																																																																																																																																																																													
E10015	X/G 16/16																																																																																																																																																																													
E10016	X/G 16/16																																																																																																																																																																													
E10018	M/X/G 20/16/16																																																																																																																																																																													
E11010	G 15																																																																																																																																																																													
E11011	G 15																																																																																																																																																																													
E11013	G 13																																																																																																																																																																													
E11015	G 15																																																																																																																																																																													
E11016	G 15																																																																																																																																																																													
E11018	M 20																																																																																																																																																																													
E12010	G 14																																																																																																																																																																													
E12011	G 14																																																																																																																																																																													
E12013	G 11																																																																																																																																																																													
E12015	G 14																																																																																																																																																																													
E12016	G 14																																																																																																																																																																													
E12018	G/M/M1 14/18/18																																																																																																																																																																													
<table border="1"> <thead> <tr> <th rowspan="2">Symbol</th> <th colspan="2">Tensile Strength</th> <th colspan="2">Yield Strength</th> </tr> <tr> <th>(Ksi)</th> <th>(N/mm<sup>2</sup>)</th> <th>(Ksi)</th> <th>(N/mm<sup>2</sup>)</th> </tr> </thead> <tbody> <tr> <td>70</td> <td>70</td> <td>480</td> <td>60</td> <td>415</td> </tr> <tr> <td>80</td> <td>80</td> <td>550</td> <td>67</td> <td>460</td> </tr> <tr> <td>90</td> <td>90</td> <td>620</td> <td>77</td> <td>530</td> </tr> <tr> <td>100</td> <td>100</td> <td>690</td> <td>87</td> <td>600</td> </tr> <tr> <td>110</td> <td>110</td> <td>760</td> <td>97</td> <td>670</td> </tr> <tr> <td>120</td> <td>120</td> <td>830</td> <td>107</td> <td>8</td> </tr> </tbody> </table>		Symbol	Tensile Strength		Yield Strength		(Ksi)	(N/mm <sup>2</sup> )	(Ksi)	(N/mm <sup>2</sup> )	70	70	480	60	415	80	80	550	67	460	90	90	620	77	530	100	100	690	87	600	110	110	760	97	670	120	120	830	107	8	<p>F=Flat V=Vertical OH=Overhead Horizontal H=Fillets=Horizontal Fillets V Down=Vertical With Downward Progression</p>																																																																																																																																					
Symbol	Tensile Strength		Yield Strength																																																																																																																																																																											
	(Ksi)	(N/mm <sup>2</sup> )	(Ksi)	(N/mm <sup>2</sup> )																																																																																																																																																																										
70	70	480	60	415																																																																																																																																																																										
80	80	550	67	460																																																																																																																																																																										
90	90	620	77	530																																																																																																																																																																										
100	100	690	87	600																																																																																																																																																																										
110	110	760	97	670																																																																																																																																																																										
120	120	830	107	8																																																																																																																																																																										
<table border="1"> <tbody> <tr> <td>1</td> <td>All Welding Positions</td> </tr> <tr> <td>2</td> <td>Horizontal And Flat Welding Positions</td> </tr> </tbody> </table>		1	All Welding Positions	2	Horizontal And Flat Welding Positions	<table border="1"> <thead> <tr> <th rowspan="2">Symbol</th> <th rowspan="2">Types Of Electrodes</th> <th colspan="5">Chemical Composition Of the Weld Metals %</th> </tr> <tr> <th>C</th> <th>Mn</th> <th>Ni</th> <th>Cr</th> <th>Mo</th> </tr> </thead> <tbody> <tr> <td>Exxxx-A1</td> <td>Carbon Molybdenum Alloyed</td> <td>0.12</td> <td>0.60</td> <td>-</td> <td>-</td> <td>0.40-0.65</td> </tr> <tr> <td>Exxxx-B1</td> <td rowspan="9">Chromium Molybdenum Alloyed</td> <td>0.05-0.12</td> <td>0.90</td> <td>-</td> <td>0.40-0.65</td> <td>0.40-0.65</td> </tr> <tr> <td>Exxxx-B2</td> <td>0.05-0.12</td> <td>0.90</td> <td>-</td> <td>1.00-1.50</td> <td>0.40-0.65</td> </tr> <tr> <td>Exxxx-B3</td> <td>0.05-0.12</td> <td>0.90</td> <td>-</td> <td>2.00-2.50</td> <td>0.90-1.20</td> </tr> <tr> <td>Exxxx-B4L</td> <td>0.05</td> <td>0.90</td> <td>-</td> <td>1.75-2.25</td> <td>0.40-0.65</td> </tr> <tr> <td>Exxxx-B5</td> <td>0.07-0.15</td> <td>0.40-0.70</td> <td>-</td> <td>0.40-0.60</td> <td>1.00-1.25</td> </tr> <tr> <td>Exxxx-B6</td> <td>0.05-0.10</td> <td>1.00</td> <td>0.40</td> <td>4.00-6.00</td> <td>0.45-0.65</td> </tr> <tr> <td>Exxxx-B7</td> <td>0.05-0.10</td> <td>1.00</td> <td>0.40</td> <td>6.00-8.00</td> <td>0.45-0.65</td> </tr> <tr> <td>Exxxx-B8</td> <td>0.05-0.10</td> <td>1.00</td> <td>0.40</td> <td>8.00-10.5</td> <td>0.85-1.20</td> </tr> <tr> <td>Exxxx-B9</td> <td>0.08-0.13</td> <td>1.25</td> <td>1.00</td> <td>8.00-10.5</td> <td>0.85-1.20</td> </tr> <tr> <td>Exxxx-C1</td> <td rowspan="5">Nickel Alloyed</td> <td>0.12</td> <td>1.25</td> <td>2.00-2.75</td> <td>-</td> <td>-</td> </tr> <tr> <td>Exxxx-C2</td> <td>0.12</td> <td>1.25</td> <td>3.00-3.75</td> <td>-</td> <td>-</td> </tr> <tr> <td>Exxxx-C3</td> <td>0.12</td> <td>0.40-1.25</td> <td>0.80-1.10</td> <td>0.15</td> <td>0.35</td> </tr> <tr> <td>Exxxx-C4</td> <td>0.10</td> <td>1.25</td> <td>1.10-2.00</td> <td>-</td> <td>-</td> </tr> <tr> <td>Exxxx-C5</td> <td>0.05</td> <td>0.40-1.00</td> <td>6.00-7.25</td> <td>-</td> <td>-</td> </tr> <tr> <td>Exxxx-NM1</td> <td>Nickel Molybdenum Alloyed</td> <td>0.10</td> <td>0.80-1.25</td> <td>0.80-1.10</td> <td>0.10</td> <td>0.40-0.65</td> </tr> <tr> <td>Exxxx-D1</td> <td rowspan="3">Manganese Molybdenum Alloyed</td> <td>0.12</td> <td>1.00-1.75</td> <td>0.90</td> <td>-</td> <td>0.25-0.45</td> </tr> <tr> <td>Exxxx-D2</td> <td>0.15</td> <td>1.65-2.00</td> <td>0.90</td> <td>-</td> <td>0.25-0.45</td> </tr> <tr> <td>Exxxx-D3</td> <td>0.12</td> <td>1.00-1.80</td> <td>0.90</td> <td>-</td> <td>0.40-0.65</td> </tr> <tr> <td>XXXX-G</td> <td>Low Alloy Electrode</td> <td colspan="5">Mn: 1.00 - Si: 0.80 - Ni: 0.50 - Cr: 0.30 Mo: 0.20 V: 0.10 When At Least One Of These Elements Exceeds The Limit, Designated With "G"</td> </tr> <tr> <td>Exxxx-M</td> <td>Military Similar Electrode</td> <td>0.10</td> <td>0.60-1.25</td> <td>1.40-1.80</td> <td>0.15</td> <td>0.35</td> </tr> <tr> <td>Exxxx-P1</td> <td>Pipeline Electrodes</td> <td>0.20</td> <td>1.20</td> <td>1.00</td> <td>0.30</td> <td>0.50</td> </tr> <tr> <td>Exxxx-W1</td> <td rowspan="2">Weathering Steel Electrodes</td> <td>0.12</td> <td>0.40-0.70</td> <td>0.20-0.40</td> <td>0.15-0.30</td> <td>Cu: 0.3-0.6</td> </tr> <tr> <td>Exxxx-W2</td> <td>0.12</td> <td>0.50-1.30</td> <td>0.40-0.80</td> <td>0.45-0.70</td> <td>Cu: 0.3-0.75</td> </tr> </tbody> </table>				Symbol	Types Of Electrodes	Chemical Composition Of the Weld Metals %					C	Mn	Ni	Cr	Mo	Exxxx-A1	Carbon Molybdenum Alloyed	0.12	0.60	-	-	0.40-0.65	Exxxx-B1	Chromium Molybdenum Alloyed	0.05-0.12	0.90	-	0.40-0.65	0.40-0.65	Exxxx-B2	0.05-0.12	0.90	-	1.00-1.50	0.40-0.65	Exxxx-B3	0.05-0.12	0.90	-	2.00-2.50	0.90-1.20	Exxxx-B4L	0.05	0.90	-	1.75-2.25	0.40-0.65	Exxxx-B5	0.07-0.15	0.40-0.70	-	0.40-0.60	1.00-1.25	Exxxx-B6	0.05-0.10	1.00	0.40	4.00-6.00	0.45-0.65	Exxxx-B7	0.05-0.10	1.00	0.40	6.00-8.00	0.45-0.65	Exxxx-B8	0.05-0.10	1.00	0.40	8.00-10.5	0.85-1.20	Exxxx-B9	0.08-0.13	1.25	1.00	8.00-10.5	0.85-1.20	Exxxx-C1	Nickel Alloyed	0.12	1.25	2.00-2.75	-	-	Exxxx-C2	0.12	1.25	3.00-3.75	-	-	Exxxx-C3	0.12	0.40-1.25	0.80-1.10	0.15	0.35	Exxxx-C4	0.10	1.25	1.10-2.00	-	-	Exxxx-C5	0.05	0.40-1.00	6.00-7.25	-	-	Exxxx-NM1	Nickel Molybdenum Alloyed	0.10	0.80-1.25	0.80-1.10	0.10	0.40-0.65	Exxxx-D1	Manganese Molybdenum Alloyed	0.12	1.00-1.75	0.90	-	0.25-0.45	Exxxx-D2	0.15	1.65-2.00	0.90	-	0.25-0.45	Exxxx-D3	0.12	1.00-1.80	0.90	-	0.40-0.65	XXXX-G	Low Alloy Electrode	Mn: 1.00 - Si: 0.80 - Ni: 0.50 - Cr: 0.30 Mo: 0.20 V: 0.10 When At Least One Of These Elements Exceeds The Limit, Designated With "G"					Exxxx-M	Military Similar Electrode	0.10	0.60-1.25	1.40-1.80	0.15	0.35	Exxxx-P1	Pipeline Electrodes	0.20	1.20	1.00	0.30	0.50	Exxxx-W1	Weathering Steel Electrodes	0.12	0.40-0.70	0.20-0.40	0.15-0.30	Cu: 0.3-0.6	Exxxx-W2	0.12	0.50-1.30	0.40-0.80	0.45-0.70	Cu: 0.3-0.75
1	All Welding Positions																																																																																																																																																																													
2	Horizontal And Flat Welding Positions																																																																																																																																																																													
Symbol	Types Of Electrodes	Chemical Composition Of the Weld Metals %																																																																																																																																																																												
		C	Mn	Ni	Cr	Mo																																																																																																																																																																								
Exxxx-A1	Carbon Molybdenum Alloyed	0.12	0.60	-	-	0.40-0.65																																																																																																																																																																								
Exxxx-B1	Chromium Molybdenum Alloyed	0.05-0.12	0.90	-	0.40-0.65	0.40-0.65																																																																																																																																																																								
Exxxx-B2		0.05-0.12	0.90	-	1.00-1.50	0.40-0.65																																																																																																																																																																								
Exxxx-B3		0.05-0.12	0.90	-	2.00-2.50	0.90-1.20																																																																																																																																																																								
Exxxx-B4L		0.05	0.90	-	1.75-2.25	0.40-0.65																																																																																																																																																																								
Exxxx-B5		0.07-0.15	0.40-0.70	-	0.40-0.60	1.00-1.25																																																																																																																																																																								
Exxxx-B6		0.05-0.10	1.00	0.40	4.00-6.00	0.45-0.65																																																																																																																																																																								
Exxxx-B7		0.05-0.10	1.00	0.40	6.00-8.00	0.45-0.65																																																																																																																																																																								
Exxxx-B8		0.05-0.10	1.00	0.40	8.00-10.5	0.85-1.20																																																																																																																																																																								
Exxxx-B9		0.08-0.13	1.25	1.00	8.00-10.5	0.85-1.20																																																																																																																																																																								
Exxxx-C1	Nickel Alloyed	0.12	1.25	2.00-2.75	-	-																																																																																																																																																																								
Exxxx-C2		0.12	1.25	3.00-3.75	-	-																																																																																																																																																																								
Exxxx-C3		0.12	0.40-1.25	0.80-1.10	0.15	0.35																																																																																																																																																																								
Exxxx-C4		0.10	1.25	1.10-2.00	-	-																																																																																																																																																																								
Exxxx-C5		0.05	0.40-1.00	6.00-7.25	-	-																																																																																																																																																																								
Exxxx-NM1	Nickel Molybdenum Alloyed	0.10	0.80-1.25	0.80-1.10	0.10	0.40-0.65																																																																																																																																																																								
Exxxx-D1	Manganese Molybdenum Alloyed	0.12	1.00-1.75	0.90	-	0.25-0.45																																																																																																																																																																								
Exxxx-D2		0.15	1.65-2.00	0.90	-	0.25-0.45																																																																																																																																																																								
Exxxx-D3		0.12	1.00-1.80	0.90	-	0.40-0.65																																																																																																																																																																								
XXXX-G	Low Alloy Electrode	Mn: 1.00 - Si: 0.80 - Ni: 0.50 - Cr: 0.30 Mo: 0.20 V: 0.10 When At Least One Of These Elements Exceeds The Limit, Designated With "G"																																																																																																																																																																												
Exxxx-M	Military Similar Electrode	0.10	0.60-1.25	1.40-1.80	0.15	0.35																																																																																																																																																																								
Exxxx-P1	Pipeline Electrodes	0.20	1.20	1.00	0.30	0.50																																																																																																																																																																								
Exxxx-W1	Weathering Steel Electrodes	0.12	0.40-0.70	0.20-0.40	0.15-0.30	Cu: 0.3-0.6																																																																																																																																																																								
Exxxx-W2		0.12	0.50-1.30	0.40-0.80	0.45-0.70	Cu: 0.3-0.75																																																																																																																																																																								
<p>X: B1, B2, B3, B4L, B5, B6, B6L, B7, B7L, B8, B8L, B9, C1, C1L, C2, C2L, C5L, D1, D2, D3, P1</p>																																																																																																																																																																														

Email : sales@terrSol.com | Web : www.terrSol.com

Index